Can-am. MAVERICK X3 X mr TURBO

HIGHLIGHTS

Rear

Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
120 hp turbocharged Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
• 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High torque Dynamic Power Steering (DPS™) • 18 in. suspension travel • FOX¹ 2.5 PODIUM¹ QS3 piggyback shocks • 14 in. aluminum wheels • Rear tow hook
Smart-Lok* front differential Snorkeled engine air intake and CVT 30 in. ITP¹ Cryptid¹ tires Front bumper, half-doors Front tow hook HMWPE full skid plate 4,500 lb (2,041kg) winch with synthetic rope X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature Painted color

ENGINE	TURBO
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid cooled and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT, high-airflow with strategically positioned CVT air intake and exhaust, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double arched A-arm with sway bar/18 in. (45.7 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/18 in. (45.7 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum with machined finish
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers



Iron Gray & Manta Green / TURBO

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,664 lb (754.8 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

10.5 gal (40 L)
7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Lighter type DC outlet in central console
RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
LED headlights and tail lights with unique Can-Am LED signature
4,500 lb (2,041 kg) winch with synthetic rope
Front bumper Half-doors Front and rear tow hooks HMWPE full skid plate

WARRANTY & EXTENDED SERVICE

EXTENDED CENTICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers