

can-am[®]




OUTLANDER XT

2022

HIGHLIGHTS

- Rotax[®] V-Twin engine options
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- Heavy-duty front and rear bumpers
- Handlebar wind deflectors
- Painted plastics for premium look
- 14 in. cast-aluminum wheels
- 26 in. ITP Terracross radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- 650 W magneto
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 5.7 gal (21.4 L) water-resistant rear compartment



-  Oxford Blue / 650 / 850 / 1000R
-  Boreal Green / 650 / 850 / 1000R
-  Mossy Oak[®] Break-Up Country Camo / 650 / 850 / 1000R

ENGINES	650	850	1000R
Type	62 hp, Rotax 650 cc V-twin, liquid-cooled	78 hp, Rotax 854 cc V-twin, liquid-cooled	91 hp, Rotax 976 cc V-twin, liquid-cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	Intelligent Throttle Control (ITC [™]) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/L, standard engine braking		
Drive Train	Selectable 2WD/4WD with Visco-Lok [†] QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

TIRES & WHEELS

Front Tires	ITP Terracross 26 x 8 x 14 in.
Rear Tires	ITP Terracross 26 x 10 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

	650	850	1000R
Estimated Dry Weight*	749 lb (341 kg)	800 lb (363 kg)	826 lb (375 kg)
L x W x H	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	11 in. (27.9 cm)		
Seat Height	34.5 in. (87.7 cm)		
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	1,650 lb (750 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES

Gauge	4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock	
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)	
Anti-Theft System	N/A	RF Digitally Encoded Security System (D.E.S.S. [™])
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
Seat	Standard	
Protection	Heavy-duty front and rear bumpers Handlebar wind deflectors Mudguards	

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

©2022 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-900-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

