

## **HIGHLIGHTS**

- · Rotax® V-Twin engine
- Visco-4Lok† front differential
- Arched double A-arm front suspension with front sway bar
- Torsional Trailing arm Independent (TTI) rear suspension
- Front and rear FOX 1.5 PODIUM
- 30 in. ITP Cryptid tires
- Intelligent Throttle Control (iTC™) with riding modes
- 14 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- · Relocated radiator
- 3,500 lb (1,588 kg) winch
- Heavy-duty front and rear bumpers
- Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- 650 W magneto
- X-package coloration, graphics and seat cover
- Mudguards



Desert Tan / 850

ENGINE	850
Туре	78 hp, Rotax 854 cc V-twin, snorkeled, liquid-cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking
Drive Train	Selectable 2WD/4WD/Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX 1.5 PODIUM
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 9 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

## DIMENSIONS & CAPACITIES

Estimated Dry Weight*	990 lb (450 kg)
LxWxH	88 x 50 x 51.5 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	36.75 in. (93.3 cm)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

<b>FEATURES</b>
-----------------

Gauge	7.6 in. wide digital display: speedometer,
	tachometer, odometer, trips and hour meters,
	gear position, 4 x 4 indicator, temperature,
	engine lights, electronic fuel gauge and clock
Instrumentation	Lighter-type DC outlet in console,
	standard connector in the back (15 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors
	and dual 55 W reflectors with tail light/brake light
Winch	3,500 lb (1,588 kg) winch
Seat	Standard
Protection	Heavy-duty front and rear bumpers
	Mud-riding footrests
	Mudguards

## WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

