2022

COMMANDER MAX XT-P 1000R

HIGHLIGHTS

PERFORMANCE	 Proven Rotax engine Dependable drivetrain Sport segment-worthy suspension
WORKABILITY	 Rugged taskmaster Work-oriented functionality Vehicle protection and rigidity
DESIGN & ERGONOMICS	Interior focused on comfort Superior fit and finish Low cost of ownership
PLATFORM FEATURES	 120.6 in. wheelbase 13 in. ground clearance 15 in. suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
SPECIFIC TO XT-P PACKAGE	64 in. wide with arched double A-arm Smart-Lok* front differential FOX' 2.5 PODIUM QS3 Piggyback shocks 30 in. XPS Hammer Force tires 15 in. cast-aluminum beadlock wheels XT front bumper 4,500 lb (2,014 kg) winch Full roof and panoramic mirror 7.6 in. digital display with keypad LED headlight and Can-Am LED signature Painted-color and special-edition seats

ENGINE	1000R
Гуре	100 hp, Rotax® 976 cc, V-tv

Type	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode / 2WD/4WD TRAIL / 4WD TRAIL ACTIV with exclusive Smart-Lok *technology.
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/14 in. (35.6 cm) travel
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	Arched TTA with sway bar/14 in. (35.6 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment

TIRES & WHEELS

Front Tires	XPS Hammer Force 30 x 10 x 15 in.
Rear Tires	XPS Hammer Force 30 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



DIMENSIONS & CAPACITIES

Estimated Dry Weight	2,000 lb (907.2 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	160.4 x 64 x 76.7 in. (407.3 x 162.6 x 194.8 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13.5 in. (34.3 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO TM modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

