



		2024 Can-Am Outlander 500	2024 Polaris Sportsman 450 H.O	2024 Yamaha Kodiak 450
Engine	✓	650cc, Rotax single cylinder, DOHC (Double Overhead Camshaft)	499cc, single cylinder, SOHC (Single Overhead Camshaft)	421cc, single cylinder, SOHC (Single Overhead Camshaft)
Horsepower	🏆	40 hp	33 hp	27 hp
Transmission	✓	CVT with engine braking	CVT without engine braking	CVT with engine braking
Suspensions	✓	Front: Double A-arm Rear: Double A-Arm	Front: MacPherson Strut Rear: Double A-Arm	Front: Double A-arm Rear: Double A-Arm
Suspension travel	🏆	Front: 9.75 in. (24.8 cm) Rear: 10.25 in. (26 cm)	Front: 8.2 in. (20.8 cm) Rear: 9.5 in. (24.1 cm)	Front: 6.7 in. (17 cm) Rear: 7.4 in. (18.8 cm)
Wheels & Tires	✓	12 in. steel wheels & 25 in. tires	12 in. steel wheels & 25 in. tires	12 in. steel wheels & 25 in. tires
Wheelbase	✓	53 in (134.5 cm)	50.5 in (128.3 cm)	48.8 in (123.9 cm)
Ground clearance	🏆	12 in. (30.5 cm)	11.5 in (29 cm)	9.6 in (24.4 cm)
Rack capacity	🏆	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)	Front: 90 lb (40.8 kg) Rear: 180 lb (81.6 kg)	Front: 88 lb (40 kg) Rear: 176 lb (79.8 kg)
Storage	✓	Front weather-tight dropdown storage, Rear open dropdown storage	Front weather-tight storage, Front rack extender	Underseat storage, Front and rear flat racks
Towing capacity	🏆	1,830 lb (830 kg)	1,350 lb (612 kg)	1,322 lb (600 kg)
Protection		Full 5.5 mm heavy-duty skid plate	Steel skid plate	Full 3 mm skid plate, front bumper
Standard platform features	✓	LED Headlights/Taillights, 4.5 in. digital display, rubber mounted bushing	Halogen headlights, 2 in. digital display, regular bushing	Halogen headlights, 4 in. digital display, regular bushing
Cost of ownership	🏆	No break-in maintenance Maintenance every 100 hours or 2,000 miles	Break-in maintenance Maintenance every 25 hours	Break-In maintenance Maintenance Every 160 hours

🏆 Industry class-leading

©2023 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A., call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext.227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.





		2024 Can-Am Outlander 500	2024 Honda Rubicon DCT	2023 CFMOTO CForce 500
Engine	✓	650cc, Rotax single cylinder, DOHC (Double Overhead Camshaft)	518cc, longitudinally mounted single-cylinder, OHV (Overhead valve engine)	495cc, single cylinder, SOHC (single Overhead Camshaft)
Horsepower	🏆	40 hp	30 hp	38 hp
Transmission		CVT with engine braking	Automatic dual-clutch transmission (DCT) with engine braking	CVT with engine braking
Suspensions	✓	Front: Double A-arm Rear: Double A-Arm	Front: Double A-Arm Rear: Double A-Arm	Front: Double A-Arm Rear: Double A-Arm
Suspension travel	🏆	Front: 9.75 in. (24.8 cm) Rear: 10.25 in. (26 cm)	Front: 7.3 in. (18.4 cm) Rear: 8.5 in. (21.6 cm)	Front: 7.5 in (19 cm) Rear: 8.9 in. (22.6 cm)
Wheels & Tires		12 in. steel wheels & 25 in. tires	12 in. steel wheels & 25 in. tires	12 in. cast-aluminum wheels & 25 in. tires
Wheelbase	✓	53 in (134.5 cm)	50.9 in. (129.3 cm)	50 in. (127 cm)
Ground clearance	🏆	12 in. (30.5 cm)	9.7 in. (24.6 cm)	10.3 in. (26.16 cm)
Rack capacity	🏆	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)	Front: 99 lb (44.9 kg) Rear: 187 lb (84.8 kg)	Front: 75 lb (34 kg) Rear: 100 lb (45.3 kg)
Storage	✓	Front weather-tight dropdown storage, Rear open dropdown storage	Front storage, Rear non-waterproof storage	Front and rear flat racks, front glovebox, rear storage
Towing capacity	🏆	1,830 lb (830 kg)	1,322 lb (599.6 kg)	873 lb (396 kg)
Protection		Full 5.5 mm heavy-duty skid plate	Full 4 mm skid plate, front bumper	Full skid plate, front bumper
Standard platform features		LED Headlights/Tailights, 4.5 in. digital display, rubber mounted bushing	Halogen headlights, 4 in. digital display, regular bushing	LED headlights, digital display, regular bushing, 2,500 lb winch
Cost of ownership	🏆	No break-in maintenance Maintenance every 100 hours or 2,000 miles	Break-in maintenance Maintenance every 100 hours	Every 100 hours

🏆 Industry class-leading

©2023 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A., call the ATV Safety Institute at 1-800-887-2827. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext.227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

