



		2004 Care Are	2024 (/
	-	2024 Can-Am COMMANDER DPS 700	2024 Kawasaki <sup>†</sup> TERYX
Engine		52 hp – 650cc Rotax® ACE ( <i>Advanced Combustion Efficiency</i> ) , single cylinder, liquid cooled, EFI	57 hp – 783cc V-twin, liquid cooled, EFI
Transmission	✓	pDrive primary CVT with engine braking and Electronic Drive Belt Protection	Automatic CVT with centrifugal clutch
Front Differential	✓	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† QE auto-locking front differential	Selectable 2WD/4WD with locking front differential
Driving Assistance	✓	Predictable engine braking system (Electronic Hill Descent Control) SPORT / ECO™ modes	Engine braking system
Suspensions type / Travel	✓	FR : Double A-arm with sway bar / 12.5 in. RR : Torsional Trailing arm (TTA) with sway bar / 13 in.	FR : Double A-arm / 8 in. RR : Double A-arm / 8.3 in.
Ground clearance	<b>√</b>	12.5 in.	11.2 in.
Wheels & Tires	<b>√</b>	14 in. steel wheels & 27 in. XPS Trail Force tires	12 in. steel wheels & 26 in. Maxxis† tires
Wheelbase	✓	90.6 in.	85.8 in.
Fuel capacity	✓	10 gal (38 L)	7.9 gal (29.9 L)
Hitch Type & Towing Capacity	✓	2 in. hitch receiver with 2,000 lb of towing capacity	2 in. hitch receiver with 1,300 lb of towing capacity
Cargo Box Dimension	✓	29.5 x 45.2 x 10.6 in. with 600 lb of capacity	27.6 x 43.3 x 10.4 in. with 600 lb of capacity
Protection	<b>√</b>	Premium half doors, mudguards, Full skid plate: Central / Transmission / Front & Rear Differentials	Quarter doors, front bumper Full skid plate: Central / Transmission / Front & Rear Differentials
Cage Type	✓	Profiled cage ROPS approved and reinforce with DP980 grade steel	Steel tube
Ergonomy	✓	Ergo-Lok cockpit with ErgoPrint bucket seats, adjustable driver seat and adjustable steering wheel	Bucket seats, adjustable driver seat
Gauge	✓	4.5 in. Digital display	3.5 in. display
Maintenance interval (miles)	<b>√</b>	Simple schedule: Every 2,000 miles* No break-in maintenance required	Complex schedule: 600 / 1,200 / 2,500 miles* Break-in maintenance required after 120 / 600 miles

EXCOZO Bombardier Recreational Products Inc (BBP). All rights reserved. 9.1M and the BRP logo are trademarked of Bombardier Recreational Products in c. or its affiliates. In the U.S.A., the products are distributed by BRP U.S. Inc., 1/4/soc-Lois is a transferrance of the production of the property of the respective owners. For other jurisdictions, see your local deletion and engineers. Reserved in the property of the respective owners. For other jurisdictions, see your local deletion and engineers. Reserved in the property of the respective owners. For other jurisdictions, proces, designed, settlems, feeting the countries of the production and produced profit productions, proces, designed, settlems, feeting the countries of the production and production of the production of t





		2024 Can-Am COMMANDER DPS 1000R	2024 Polaris <sup>†</sup> GENERAL 1000 Sport		
Engine	<b>√</b>	976cc Rotax® V-Twin, liquid cooled, EFI – 100 hp	999cc Twin-cylinder, liquid cooled, EFI – 100 hp		
Transmission	<b>√</b>	Quick Response System (QRS) CVT with Electronic Drive Belt Protection	СVТ		
Driving Assistance	✓	Predictable engine braking system (Electronic Hill Descent Control) SPORT / ECO™ modes	Engine braking system		
Suspensions type / Travel		FR : Double A-arm with sway bar / 12.5 in. RR : Torsional Trailing arm (TTA) with sway bar / 13 in.	FR : Double A-arm with stabilizer bar / 12.25 in. RR : Double Arm IRS with stabilizer bar / 13.2 in.		
Ground clearance	<b>√</b>	12.5 in.	12 in.		
Wheels & Tires		14 in. steel wheels & 27 in. XPS Trail Force tires	12 in. aluminium wheels & 27 in. CST Clincher† tires		
Wheelbase	<b>√</b>	90.6 in.	81 in.		
Fuel capacity	✓	10 gal (38 L)	9.5 gal (36 L)		
Hitch Type & Towing Capacity	<b>√</b>	2 in. hitch receiver with 2,000 lb of towing capacity	2 in. hitch receiver with 1,500 lb of towing capacity		
Cargo Box Dimension	<b>√</b>	29.5 x 45.2 x 10.6 in. with 600 lb of capacity	27.5 x 43.1 x 11.6 in. with 600 lb of capacity		
Protection	<b>√</b>	Premium half doors, mudguards, Full skid plate: Central / Transmission / Front & Rear Differentials	Half doors, mudguards Skid plate: Central / Transmission		
Cage Type	<b>√</b>	Profiled cage ROPS approved and reinforce with DP980 grade steel	Information not available		
Ergonomy	<b>√</b>	Ergo-Lok cockpit with ErgoPrint bucket seats, adjustable driver seat and adjustable steering wheel	Bolstered Bucket seats, adjustable driver seat and seat belts		
Gauge	✓	4.5 in. Digital display	4 in. LCD analog display		
Maintenance interval (miles)	<b>√</b>	Simple schedule: Every 2,000 miles*	Complex schedule: 500 / 1,000 / 2,000 / 2,500 miles*		

