

0		2024 Can-Am DEFENDER HD7	2024 Polaris <sup>†</sup> Ranger 570 Full-Size
Engine	✓	650cc Rotax® ACE single cylinder, liquid cooled, EFI – 52 hp	567cc, single cylinder, liquid cooled, EFI – 44 hp
Transmission	<b>√</b>	CVT with engine braking and Electronic Drive Belt Protection & pDrive primary clutch	CVT
Traction System		Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential	On-Demand AWD / 2WD / VersaTrac Turf Mode
Driving Assistance	✓	Electronic Hill Descent Control and ECO / ECO Off / Work driving modes	Not available
Suspensions	✓	FR : Double A-arm / 10 in. RR : Torsional Trailing Arm (TTA) with external sway bar / 10 in.	FR: MacPherson Strut / 9 in. RR: Dual A-arm / 10 in.
Wheels & Tires	✓	14 in. steel wheels & 27 in. XPS Trail Force tires	12 in. steel wheels & 25 in. Carlisle 489 tires
Wheelbase	✓	83 in.	79 in.
Ground clearance	✓	11 in.	10.5 in.
Fuel capacity	✓	10.6 gal (40 L)	9 gal (34.1 L)
Hitch Type & Towing Capacity	✓	2 in. hitch receiver with 2,500 lb (1,134 kg) of towing capacity	2 in. hitch receiver with 1,500 lb (680 kg) of towing capacity
Capacity & Versatility	<b>√</b>	4 x steel anchors / tie-down points, 4 x 5-gallon (18.9 L) pail recesses, 14 x LinQ quick-attach, 1 x 3 and plywood separators and bed extender-ready, Sturdy removable tailgate allowing for 250 lb capacity, 4 integrated cup recesses and a ruler in tailgate	Lock & Ride system
Cage Type	✓	Profiled cage ROPS approved	Tubular
Seat	✓	VERSA-PRO bench seat with passenger seats flipping up, underside hooks	Bench seat / 3-seater
Protection	✓	Integrated front steel bumper, HMWPE central skid plate	central skid plate
Gauge	✓	4.5 in. Digital display	2 in. LCD Single analog display
Lighting	<b>√</b>	Front lighting output 140 W and LED taillights	50-W Headlight and LED taillights





		2024 Can-Am DEFENDER HD9	2024 Polaris <sup>†</sup> Ranger 1000
Engine	✓	976cc Rotax® V-twin, liquid cooled, EFI – 65 hp	999cc twin cylinders SOHC, liquid cooled, EFI – 61 hp
Transmission	<b>√</b>	PRO-TORQ CVT transmission with Quick Response System, high airflow ventilation and Electronic Drive Belt Protection	CVT
Traction System		Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential	High performance True On-Demand AWD / 2WD / VersaTrac Turf Mode
Driving Assistance	✓	Electronic Hill Descent Control and ECO / ECO Off / Work driving modes	Not available
Suspensions	<b>√</b>	FR:Double A-arm / 10 in. RR:Torsional Trailing Arm (TTA) with external sway bar / 10 in.	FR : Double A-arm / 10 in. RR : Double A-arm / 10 in.
Wheels & Tires	✓	14 in. steel wheels & 27 in. XPS Trail Force tires	12-in. steel wheels with 25 in. 489 tires
Wheelbase	✓	83 in.	81 in.
Ground clearance		11 in.	12 in.
Fuel capacity		10.6 gal (40 L)	11.35 gal (43 L)
Hitch Type & Towing Capacity	<b>√</b>	2 in. hitch receiver with 2,500 lb (1,134 kg) of towing capacity	2 in. hitch receiver with 2500 lb (1134 kg) of towing capacity
Cargo box capacity	✓	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Cargo Box Versatility	<b>√</b>	4 x steel anchors / tie-down points, 4 x 5-gallon (18.9 L) pail recesses, 14 x LinQ quick-attach, 1 x 3 and plywood separators and bed extender-ready, Sturdy removable tailgate allowing for 250 lb capacity, 4 integrated cup recesses and a ruler in tailgate	Lock & Ride system
Seat	<b>√</b>	VERSA-PRO bench seat with passenger seats flipping up, underside hooks	Standard bench seat
Protection	✓	Integrated front steel bumper, HMWPE central skid plate	Central skid plate
Gauge	✓	4.5 in. Digital display	4 in. LCD display
Lighting	<b>√</b>	Front lighting output 140 W and LED taillights	55-W low / 60-W high, LED taillights

