2024 DEFENDER MAX X MR



PACKAGE HIGHLIGHTS

- · Smart-Lok*front differential
- Strategically positioned engine air intake and CVT inlet / outlet
- · Brake holding mechanism
- VERSA-PRO bolster bench seat, reinforced seat skin featuring X package trims and adjustable driver seat
- 7.6 in. digital display with keypad
- 64 in. wide with arched A-arm
- LED signature
- 30 in. XPS Swamp Force tires
- 4,500 lb (2,014 kg) relocated winch
- · Heavy-duty front steel bumper
- · Aluminum rock sliders
- · HMWPE full skid plate

Wildland Camo

| ENGINE | HD10 |
|----------------------|--|
| Туре | 82 hp / 69 lb-ft, Rotax* 976 cc, V-twin, liquid-cooled with strategically positioned engine air intake |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | PRO-TORQ CVT with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio and high-airflow ventilation with strategically positioned CVT air intake and exhaust Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD TRAIL / 4WD MUD with exclusive Smart-Lok* |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes |
| Power Steering | Dynamic Power Steering (DPS™) |
| SUSPENSIONS | |
| Front Suspension | Arched double A-arm with sway bar / 12 in. (30.5 cm) suspension travel |
| Front Shocks | Twin tube gas-charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 12 in. (30.5 cm) suspension travel |
| Rear Shocks | Twin tube gas-charged shocks |
| TIRES & WHEELS | |
| Front / Rear Tires | XPS Swamp Force 30 x 9 / 11 x 14 in. |
| Wheels | 14 in. cast aluminum |
| BRAKES | |
| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| | Brake holding mechanism |

DIMENSIONS & CAPACITIES

| age | Profiled cage, ROPS approved |
|-----------------------|--|
| stimated Dry Weight | 2,060 lb (934 kg) |
| xWxH | 161.9 x 64 x 82 in. (411.2 x 162.6 x 208.3 cm) |
| Vheelbase | 115.5 in. (294 cm) |
| Fround Clearance | 15 in. (38.1 cm) |
| argo Box Dimensions | 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm) |
| argo Box Capacity | 1,000 lb (454 kg) / California only: 600 lb (272.2 kg) |
| ower Tilt Bed | N/A |
| ailgate Load Capacity | 250 lb (113.4 kg) |
| torage Capacity | Total: 16.9 gal (63.9 L) |
| owing Capacity | 2,500 lb (1,134 kg) |
| ayload Capacity | 1,550 lb (703 kg) |
| uel Capacity | 10.6 gal (40 L) |
| erson Capacity | 6 |

| Gauge | 7.6 in. wide digital display with keypad |
|-----------------|---|
| Battery | 12 V (30 amp/h) |
| Magneto | 650 W |
| Instrumentation | DC outlet (10 A) USB port (10 A) x 2 |
| Lighting | Front lighting output 140 W LED signature LED tail lights |
| Winch | Relocated 4,500 lb (2,041 kg) winch with synthetic rope and roller fairlead |
| Seat | VERSA-PRO bolster bench seats with passenger seats flipping up Adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims |
| Steering Wheel | Adjustable tilt steering |
| Protection | Heavy-duty front steel bumper HMWPE full skid plate Aluminum rock sliderss Mudguards |
| Hitch Type | 2 in. hitch receiver |

WARRANTY & EXTENDED SERVICE

| Factory Warranty | 1 year BRP limited warranty |
|---------------------------|---|
| Extended Service Terms | B.E.S.T. term available up to 30 months |



