2024 MAVERICK X3 X RC TURBO RR 72"



PACKAGE HIGHLIGHTS

- · Smart-Lok* front differential
- FOX † 3.0 PODIUM RC2 † shocks with bypass
- · Belt monitoring system
- 850 W magneto
- · 7.6 in. digital display with keypad
- X package graphics / seats
- · 4-point harness with shoulder pads
- · Can-Am LED signature
- 15 in. aluminum beadlock wheels
- 32 in. Maxxis Liberty tires
- · Front bumper, half-doors, full roof, intrusion bar
- · Front tow hook
- 4,500 lb (2,041 kg) winch with synthetic rope
- · HMWPE differential and under bumper skid plates
- HMWPE front and rear suspension arm
- UHMWPE rock sliders

Hybrid White & Legion Red

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled
	with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology
	True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Trophy Truck inspired double arched A-arm with sway bar / 22 in. (55.9 cm) suspension travel
Front Shocks	FOX [†] 2.5 PODIUM RC2 [†] Piggyback with bypass, dual-speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing Arm X (TTX) with sway bar and arched lower links / 24 in. (61 cm) suspension travel
Rear Shocks	FOX† 3.0 PODIUM RC2† remote reservoir with bypass, dual- speed compression and rebound adjustments
TIRES & WHEELS	
Front / Rear Tires	Maxxis Liberty [†] 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,843 lb (836 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ® quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half-doors Full roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skid plates Full heavy-duty with differential / Under bumper / Front and rear suspension arm Rear tow hook Trailing Arm protector Lower A-arm protector

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



