## 2024 MAVERICK X3 X MR TURBO RR 64"



## PACKAGE HIGHLIGHTS

- · Smart-Lok\* front differential
- FOX<sup>†</sup> 2.5 PODIUM QS3<sup>†</sup> Piggyback shocks
- · Snorkeled engine air intake and CVT
- Belt monitoring system
- 850 W magneto
- 7.6 in. digital display with keypad
- X package graphics / seats
- Can-Am LED signature
- 30 in. ITP Cryptid tires
- · Front bumper, half-doors
- · Front tow hook
- 4,500 lb (2,041kg) winch with synthetic rope
- HMWPE full skid plate

## Hyper Silver & Legion Red

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-performance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double arched A-arm with sway bar / 20 in. (50.8 cm) suspension travel
Front Shocks	FOX <sup>†</sup> 2.5 PODIUM Piggyback with QS3 <sup>†</sup> compression adjustment
Rear Suspension	4-link Torsional Trailing Arm X (TTX) with sway bar and arched lower links / 20 in. (50.8 cm) suspension travel
Rear Shocks	FOX <sup>†</sup> 2.5 PODIUM Piggyback with QS3 <sup>†</sup> compression adjustment and bottom-out control
TIRES & WHEELS	
Front / Rear Tires	ITP Cryptid 30 x 9 / 11 x 14 in.
Wheels	14 in. cast-aluminum with machined finish
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

## **DIMENSIONS & CAPACITIES**

Estimated Dry Weight	1,705 lb (773.4 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ® quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half-doors Front and rear tow hooks HMWPE full skid plate
WARRANTY & EXTEN	DED SERVICE
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



