

## 2025 Can-Am MAVERICK SPORT X rc 1000R



## HOW TO WIN

**Suspension**

+2.6 in. front and +1.6 in. rear suspension travel for improved riding dynamics and comfort  
Bigger shocks 2.5 in. FOX  
Better ground clearance (+2.5 in.)

**Traction**

30 in. tires with bigger wheels, for improved riding experience

**Features**

Exclusive Smart-Lok\*  
Multiple skid plates, front bumper and rear bumper  
4,500 lb (2,041 kg) winch with synthetic cable  
Rock sliders and mudguards  
More storage capacity

## Key features

- 100 hp / 976cc Rotax ® V Twin, liquid cooled, EFI
- Quick Response System (QRS) CVT with Electronic Drive Belt Protection
- Lockable front differential with exclusive Smart-Lok\* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL
- Dynamic Power Steering (DPS)
- CVT Engine Braking
- SPORT / ECO™ modes
- 15 in. (38.1 cm) Ground Clearance
- 90.6 in. (230.1 cm) Wheelbase

**Suspension Travel:**

- FR: Arched double A-arm with sway bar / 14.8 in. (37.6 cm)
- RR: Arched TTA with sway bar / 14.8 in. (37.6 cm)

**Shocks:**

- FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment

## Additional features

- 30 in. Maxxis Liberty† tires with 14 in. Aluminum wheels
- 2 in. hitch receiver with 1,500 lb (680 kg) of towing capacity
- 10-gal (38 L) Fuel capacity
- 300 lb (136 kg) Cargo box capacity
- 5.3-gal (20.2L) Storage capacity
- Integrated front steel bumper, Premium half doors, Rear sport bumper, Mudguards, UHMWPE rock sliders
- HMWPE skid plate: Central / Transmission / Front & Rear Differentials / Front and rear suspension arm
- Ergo-Lok cockpit with ErgoPrint bucket seats, adjustable driver seat and Adjustable steering wheel
- 4,500 lb (2,041 kg) winch with synthetic cable
- LinQ and accessory ecosystem
- 7.6 in. wide digital display with keypad

## 2025 COMPARE SHEET

## 2025 Polaris† RZR Trail S 1000 Ultimate

## Key features

- 100 hp / 999cc Twin cylinder, liquid cooled, EFI
- Automatic PVT
- High performance True On Demand AWD / 2WD
- EPS (Electronic Power Steering)
- Engine braking system
- 12.5 in (31.8 cm) Ground clearance
- 79 in (200.7 cm) Wheelbase

**Suspension Travel:**

- FR: Dual A-Arm with Stabilizer Bar and 12.25 in (31.1 cm)
- RR: Dual A-Arm with Stabilizer Bar and 13.2 in (33.5 cm)

**Shocks:**

- 2 in. Walker Evans Needle Shocks with 16-Position Adjustable Clickers

## Additional features

- 27 in. tires with 12in. Aluminum wheels
- 1.5 in. hitch receiver with 1500 lb (680 kg) towing capacity
- 9.5-gal (35.9 L) Fuel capacity
- 300 lb (136 kg) Cargo box capacity
- Standard glove box and cup holders
- Half doors, full roof,
- Skid plate: Central / Transmission
- Bolstered Bucket Seats with Toolless Driver Seat Slider and Standard Passenger Seat Slider with Adjustable Tilt Steering
- Lock & Ride®
- 7 in. RIDE COMMAND with rear camera
- Premium Rockford Fosgate® Stage 2 Audio