

## 2025 Can-Am MAVERICK X3 DS TURBO



## HOW TO WIN



### Performance

Leading HP with +21 hp  
Leading Power-to-weight +1.7 hp / 100lb



### Transmission

pDrive primary and Quick Response System X (QRS-X) CVT / reduce backlash on parts and maximizes performance



### Suspension

+4 in. Front and +2 in. Rear travel  
All around 2.5 in. Shocks



### Features

Exclusive Smart-Lok\* Differential  
30in. XPS Trac force tires  
Ergo-Lok Cockpit, low seating position  
Bigger Display with keypad  
RF Digitally Encoded Security System (D.E.S.S.™)

## NEW For 2025

- New Coloration Scandi Blue & Orange Crush
- New 30 in. XPS Trac force tires

## Key features

- 135 hp / 900cc Rotax @ ACE, Turbocharged triple cylinder engine, liquid cooled, high performance air filter, EFI
- 8.7 hp / 100 lb Power-to-weight ratio
- Quick Response System X (QRS-X) CVT with high airflow & pDrive primary clutch
- Lockable front differential with exclusive Smart - Lok\* technology . True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV/ 4WD TRAIL
- 64in. (162.5 cm) Width & 14 in. (35.6 cm) Ground clearance
- 102 in. (259.1 cm) Wheelbase

### Suspension travel:

- FR : Double A-arm with sway bar / 20 in. (50.8 cm)
- RR : 4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm)

### Shocks:

- SHOWA HPG piggyback 2.5

## Additional features

- 30in. XPS Trac Force with 14 in. Aluminum wheels
- 10.5-gal (40 L) Fuel Capacity
- Ergo-Lok cockpit with four-way adjustable seats, low seating position
- LED headlights and taillights
- Integrated front bumper, quarter doors, HMWPE full skid plate, rear tow hook
- 4.5 in. digital display with keypad
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
- LinQ and accessory ecosystem

# 2025 COMPARE SHEET

## 2025 Polaris† RZR XP 1000 SPORT

## Key Features

- 114 hp / 999cc Twin-cylinder engine, liquid cooled, EFI
- 7.0 hp / 100lb power to weight ratio
- Automatic PVT transmission (CVT)
- High Performance True On-Demand AWD/2WD
- 64in. (162.5 cm) Width & 14 in. (35.6 cm) Ground clearance
- 90 in ( 228.6 cm)

### Suspension Travel:

- FR: Dual A-Arm with Stabilizer Bar / 16 in. (40.6 cm)
- RR: Trailing Arm with Stabilizer Bar / 18 in. (45.7 cm)

### Shocks:

- FR: 2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
- RR: 2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers

## Additional features

- 29in. Radial Tire with 14in. cast aluminum wheels
- 9.5 gal (36 L) Fuel Capacity
- Bolstered Bucket Seats with Driver Seat Slider Retractable 3-Point Seat Belts
- Steering Wheel with Tilt Adjustment
- White LED Low/High & Red LED Tail / Brake Lights
- Half doors, full skid plate and Front bumper
- 4 in. LCD analog display