

2025 Can-Am MAVERICK X3 DS TURBO RR



HOW TO WIN



Performance

Leading HP with +19 hp
Leading Power-to-weight +2.6 hp / 100lb



Transmission

pDrive primary and Quick Response System X (QRS-X) CVT / reduce backlash on parts and maximizes performance



Suspension

+3 in. Front travel
All around 2.5 in. Shocks



Features

Exclusive Smart-Lok* Differential
Ergo-Lok Cockpit, low seating position
Bigger Display with keypad

NEW For 2025

- New Coloration Scandi Blue & Orange Crush
- New 30 in. XPS Trac force tires

Key features

- 200 hp, 900cc, Rotax® ACE Turbocharged Triple cylinder engine, liquid cooled, with integrated intercooler and high-performance air filter, EFI
- Power to weight: 12.9 hp / 100 lb
- High Torque Tri - Mode Dynamic Power Steering
- Quick Response System X (QRS-X) CVT with high airflow & pDrive primary clutch
- Lockable front differential with exclusive Smart - Lok* technology. True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV/ 4WD TRAIL
- 64in. (162.5 cm) Width & 14 in. (35.6 cm) Ground clearance
- 102 in. (259.1 cm) Wheelbase

Suspension travel:

- FR : Double A-arm with sway bar / 20 in. (50.8 cm)
- RR : 4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm)

Shocks:

- SHOWA HPG piggyback 2.5

Additional features

- 30in. XPS Trac Force with 14 in. Aluminum wheels
- 10.5-gal (40 L) Fuel Capacity
- Ergo-Lok cockpit with four-way adjustable seats, low seating position
- LED headlights and taillights
- Integrated front bumper, quarter doors, HMWPE full skid plate, rear tow hook
- 4.5 in. digital display with keypad
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
- LinQ and accessory ecosystem

2025 COMPARE SHEET

2025 Polaris† RZR PRO XP SPORT

Key Features

- 181 hp, 925 cc, 925cc Turbocharged Twin cylinder engine, liquid cooled with intercooler, EFI
- Power to weight: 10.3 hp / 100 lb
- EPS
- Automatic PVT transmission (CVT)
- Isolated Xtreme Performance True On-Demand AWD/2WD
- 64in. (162.5 cm) Width & 14.5 in (36.8 cm) Ground clearance
- 96 in (244 cm)

Suspension Travel:

- FR: Dual A-Arm with Stabilizer Bar / 17 in (43.2 cm)
- RR: Trailing Arm & Radius Rods with Stabilizer Bar / 20 in (50.8 cm)

Shocks:

- FR: 2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
- RR: 2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers

Additional features

- 30 in. Tires with 14in. cast aluminum wheels
- 12-gal (45.4 L) Fuel Capacity
- Bolstered Bucket Seats with 4-way adjustability and 3-Pt Height Adjustable Seat Belts and Steering Wheel with Tilt Adjustment
- White LED Low/High & Red LED Tail / Brake Lights
- Half doors, full skid plate and Front bumper
- 4 in. Color LCD display
- Polaris P.A.S.S Anti-Theft System