2025 OUTLANDER MAX XT 850 / 1000R



PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Intelligent Engine Braking (iEB $^{\!\scriptscriptstyle\mathsf{TM}}\!$) and driving modes
- Visco-Lok[†] QE auto-locking front differential
- · 26 in. XPS Trail King 2 dedicated trail
- 14 in. aluminum wheels
- 3,500 lb winch
- 7.6 in. wide digital display
- · Full skid plate, front bumper, rear bumper
- · Phone storage and USB charger
- · Front dropdown storage
- · Rear removable storage

DIMENSIONS &

1000R

850 package highlights plus 1000R exclusive features:

Performance features:

- Visco-4Lok
- Specific CVT calibration
- High flow radiator cooling fan of 120W & 500 cm3
- 4-discs braking system
- Front sway bar

Aesthetic features:

- LED signature lights
- Extra painted panels

	Platinum Satin / 850 / 1000R
	Fiery Red / 850 / 1000R
	Wildland Camo / 850 / 1000F

ENGINES	850	1000R	
Туре	82 hp / 66 lb-ft, Rotax 999 cc V-twin, DOHC, liquid cooled. Radiator cooling fan of 80W and 150 cm3	101 hp / 69 lb-ft, Rotax 999 cc V-twin, DOHC, liquid cooled. High flow radiator cooling fan of 120W and 500 cm3	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	pDrive primary CVT L / H / N / R / P	pDrive primary CVT with specific calibration L/H/N/R/P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential	
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)		
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)		
SUSPENSIONS			
Front Suspension	Arched Double A-arm 10.8 in. (27.4 cm) travel	Arched Double A-arm with sway bar 10.8 in. (27.4 cm) travel	
Front Shocks	Twin-tube		
Rear Suspension	Arched Double A-arm 12 in. (30.5 cm) travel		
Rear Shocks	Twin-tube		
TIRES & WHEELS			
Front / Rear Tires	XPS Trail King 2 - 26 x 8/10 x 14 in.		
Wheels	14 in. aluminum		
BRAKES			
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Dual 214 mm disc brakes with hydraulic twin-piston calipers	

CAPACITIES	850	1000R	
Estimated Dry Weight*	998 lb (453 kg)		
LxWxH	99 x 48.5 x 56.4 in. (252 x 123.2 x 143.2 cm)		
Wheelbase	60.8 in. (154.4 cm)		
Ground Clearance	11.5 in. (29.2 cm)		
Seat Height	37.8 in. (96 cm)		
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)		
Storage Capacity	10.6 gal (40 L)		
Towing Capacity	1,830 lb (830 kg)		
Fuel Capacity	5.1 gal (19.5 L)		
FEATURES			
Gauge	7.6 in. wide digital display		
Instrumentation	Phone storage & USB charger		
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)		
Lighting	LED headlights and taillights	LED headlights and taillights LED signature	
Winch	3,500 lb (1,588 kg) winch		
Seat	Standard		
Handlebar Standard			
Protection	Full skid plate, front bumper, rear bumper		
WARRANTY & EXTENI	DED SERVICE		
Factory Warranty	6-month BRP limited warranty		
Extended Service B.E.S.T. term available up to 36 months Terms		months	



