## **2025 COMMANDER MAX XT**



## PACKAGE HIGHLIGHTS

- 64 in. wide with arched A-arm
- 7.6 in. digital display with keypad
- · Can-Am LED signature
- 28 in. XPS Trail King tires
- 14 in. aluminum wheels
- XT front bumper

**DIMENSIONS &** 

Terms

- 4,500 lb (2,014 kg) winch
- Full roof

Fiery Red / 700 / 1000R
Triple Black / 700 / 1000B

Fuel Delivery System I i Transmission I Drive Train	52 hp / 42 lb-ft, Rotax* ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid-cooled Intelligent Throttle Control (iTC injection (EFI) pDrive primary CVT with engine braking and electronic drive belt protection L / H / N / R / P  Selectable Turf Mode / 2WD / 4WD with Visco-Lok* QE auto-locking	Quick Response System (QRS) CVT with high-airflow ventilation and electronic drive belt protection Extra-L / H / N / R / P Selectable Turf	
Transmission Prive Train S	injection (EFI) pDrive primary CVT with engine braking and electronic drive belt protection L / H / N / R / P  Selectable Turf Mode / 2WD / 4WD with	Quick Response System (QRS) CVT with high-airflow ventilation and electronic drive belt protection Extra-L / H / N / R / P Selectable Turf	
Drive Train	engine braking and electronic drive belt protection L / H / N / R / P Selectable Turf Mode / 2WD / 4WD with	(QRS) CVT with high-airflow ventilation and electronic drive belt protection Extra-L / H / N / R / P Selectable Turf	
1	Mode / 2WD / 4WD with		
	front differential	Mode / 2WD / 4WD auto-locking front differential	
	CVT Engine Braking SPORT / ECO™ modes		
Power Steering [	Dynamic Power Steering (DPS™)		
SUSPENSIONS			
· .	Double A-arm with sway bar / 12.5 in. (31.8 cm) suspension travel	Arched double A-arm with sway bar / 15 in. (38.1 cm) suspension travel	
Front Shocks	Twin-tube gas-charged shocks		
·	TTA with sway bar / 13 in. (33 cm) suspension travel	Arched TTA with sway bar / 15 in. (38.1 cm) suspension travel	
Rear Shocks	Twin-tube gas-charged shocks		
TIRES & WHEELS			
Front / Rear Tires	XPS Trail King 28 x 9/11 x 14 in.		
Wheels	14 in. cast aluminum		
BRAKES			
Front / Rear	D 1000 II I I III	hydraulic twin-piston calipers	

CAPACITIES	700	1000R	
Estimated Dry Weight	1,874 lb (852 kg)	1,930 lb (875.4 kg)	
Chassis / Cage	Profiled cage, ROPS-approved	-	
LxWxH	160.4 x 64 x 76.2 in. (407.4 x 16	2.6 x 193.5 cm)	
Wheelbase	120.6 in. (306.3 cm)		
Ground Clearance	13 in. (33 cm)		
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114	1.7 x 27 cm)	
Cargo Box Capacity	600 lb (272.2 kg)		
Towing Capacity	2,000 lb (907.2 kg)		
Payload Capacity	1,280 lb (580.6 kg)		
Storage Capacity	Total: 8.5 gal (32.1 L)		
Fuel Capacity	10 gal (38 L)		
FEATURES			
Gauge	7.6 in. wide digital display with	keypad	
Instrumentation	DC outlet (10 A)		
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button		
Magneto	650 W		
Lighting	Front lighting output 110 W LED signature LED taillights		
Winch	4,500 lb (2,041 kg) winch with a	oller fairlead	
Steering Wheel	Adjustable tilt steering		
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof		
Hitch Type	2 in. hitch receiver		
WARRANTY & EXTENI	DED SERVICE		
Factory Warranty	6-month BRP limited warranty		
Extended Service	B.E.S.T. term available up to 30	months	



