2025 MAVERICK R X





ENGINE	999T DCT
Туре	240 hp, Rotax* 999T engine, 999 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax® DCT, 7-speed with high and low range
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	Gen 2 Tri-mode DPS™ high torque
SUSPENSIONS	
Front Suspension	Forged-aluminum heavy-duty tall knuckle Double A-arm with sway bar / 25 in. (63.5 cm) suspension travel
Front Shocks	FOX [†] 2.5 PODIUM Piggyback with QS3 [†] compression adjustment
Rear Suspension	4-link trailing arm with forged-aluminum heavy-duty tall knuckle / 25 in. (63.5 cm) suspension travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment and bottom-out control
TIRES & WHEELS	
Front / Rear Tires	ITP Tenacity XNR 30 x 10 x 15 in.
Wheels	15 in. aluminum flow-formed
BRAKES	
Front	32 mm hydraulic triple-piston caliper with a 265 mm disc
Rear	30 mm hydraulic twin-piston caliper with a 255 mm disc

PACKAGE HIGHLIGHTS

- 77 in. 4-link trailing arm with aluminum HD tall knuckle
- Smart-Lok™* front differential
- FOX[†] 2.5 PODIUM Piggyback with QS3[†] compression adjustment and bottom-out control
- 10.25 in. touchscreen display
- 30 in. ITP Tenacity XNR tires
- 15 in. flow-formed wheels
- Rear camera
- Telescopic steering wheel with infotainment controls
- Full hard roof
- · Full plastic skid plate
- · 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature
- Center dashboard storage with cell phone holder
- X package graphics / seats
- 1,700 W magneto

Terms

DIMENSIONS & CAPACITIES

Estimated Dry Weight	2,225 lb (1,009 kg)
Chassis / Cage	High-strength (dual-phase) steel tubing and stampings
LxWxH	138.7 x 78.1 x 70.4 in. (352.2 x 198.5 x 177.8 cm)
Wheelbase	108 in. (274.3 cm)
Ground Clearance	17 in. (43.2 cm)
Rack Capacity	200 lb (90 kg)
Storage Capacity	Total: 2.1 gal (8.1 L)
Fuel Capacity	13.2 gal (50 L)
FEATURES	
Gauge	4.5 in. wide digital display with keypad and 10.25 in. touchscreen display
Instrumentation	USB A (charging port and communication port) DC outlet (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	Premium high-performance LED headlights Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch-ready bumper (not installed)
Magneto	1,700 W
Protection	Full hard roof Premium half doors Front lower deflector Front / rear anchor Full plastic skid plate
WARRANTY & EXTEN	DED SERVICE
Factory Warranty	6-month BRP limited warranty
Extended Service	B.E.S.T. term available up to 30 months



