

2026 CAN-AM MAVERICK R MAX X RS WITH SMART-SHOX

COMPARISON SHEET



KEY FEATURES

240 hp, Rotax® 999T engine, 999 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter

Rotax® DCT, 7-speed with high and low range / shift on the fly

Lockable front differential with exclusive Smart-Lok® True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL

77 in. forged-aluminum heavy-duty tall knuckle

17 in. (43.2 cm) ground clearance

142.5 in. (365 cm) wheelbase

SUSPENSION TRAVEL:

FR: Double A-arm with sway bar / 24 in. (61 cm)
RR: 4-link trailing arm / 24 in. (61 cm)

SHOCKS: SMART-SHOX / LIVE VALVE GEN 3

FR: FOX® 2.5 PODIUM® Piggyback with bypass and Smart-Shox
RR: FOX® 3.0 PODIUM® Piggyback with bypass and Smart-Shox

32 in. ITP Tenacity XNR tires with 16 in. aluminum flow-formed beadlock wheels (6-lug)

10.25 in. touchscreen display with front and rear cameras

Telescopic steering wheel with infotainment controls

Premium high-performance LED headlights
Can-Am LED signature

Full roof, premium half doors, rock guards
Front / rear anchor and full plastic skid plate

13.2 gal (50 L) fuel capacity

LinQ and accessory ecosystem

ADDITIONAL FEATURES

HOW TO WIN

PERFORMANCE

Industry-leading with +15 hp
Engine modes with Anti-Lag
(ART) Technology

TRANSMISSION

Industry-first high hp 7-speed
DCT transmission
Shift on the fly high / low

SUSPENSION

Exclusive 77 in. forged-aluminum
Heavy-duty tall knuckle
Suspension travel +1.75 in. front
+1 in. ground clearance

FEATURES

+1.2 gal more fuel capacity
Bigger leg space (15%)
Exclusive Smart-Lok® differential
10.25 in. touchscreen display

2025 POLARIS† RZR PRO R 4 ULTIMATE

KEY FEATURES

225 hp, 1997 cc, 4-stroke DOHC inline four-cylinder, liquid-cooled, EFI

Automatic PVT transmission

Pro Performance True 2WD/4WD/4WD Lock

74 in. (188 cm) width and 16 in. (40.6 cm) ground clearance

133.5 in. (339 cm) wheelbase

SUSPENSION TRAVEL:

FR: Dual A-arm with 3-piece stabilizer bar 22.25 in. (56.5 cm)
RR: Trailing arm with toe link and 3-piece stabilizer bar 24.5 in. (62.2 cm)

SHOCKS: DYNAMIX DV 3.0

FR/RR: FOX® 3.0 Live Valve X2 Internal Bypass

ADDITIONAL FEATURES

32 in. Maxxis Rampage Fury tires with 15 in. aluminum beadlock wheels (5-lug pattern)

7 in. Ride Command with rear camera

Steering wheel with tilt and telescoping adjustment

Signature animated RZR Fang accent lighting white LED, low / high and red LED tail /
brake lights and interior accent lighting

Aluminum roof, mud and rock guards

Front: heated and vented bolstered bucket seats

12.3 gal fuel capacity

Rockford Fosgate stage 4 audio system