



\*Can-Am On-Road vehicles are engineered to be easy to learn and ride. Check the licence requirements in your country, in most of them you can save the effort of the motorcycle licence to enjoy open-air riding.

# **RYKER**

### **PACKAGE HIGHLIGHTS**

- · Priced to excite
- · Designed for fun
- · Easy to ride
- · 100 000 ways to make it your own



	Rotax® 600 ACE™	Rotax® 900 ACE™		
ENGINE				
Туре	Rotax® 600 ACE™ in-line 2 cylinders, liquid-cooled with electronic fuel injection and electronic throttle control	Rotax® 900 ACE™ in-line 3 cylinders, liquid-cooled with electronic fuel injection and electronic throttle control		
Bore & stroke	74 x 69,7 mm (2.9 x 2.7 in.)	74 x 69,7 mm (2.9 x 2.7 in.)		
Power	50 hp (37.3 kW) @ 7300 RPM	82 hp (61.1 kW) @ 8000 RPM		
Torque	49.7 Nm (36.7 ft-lb) @ 6000 RPM	79.1 Nm (58.3 ft-lb) @ 6500 RPM		
CO2 emissions	127 g/km	143 g/km		
Fuel consumption	43.6 mpg (5.4 l/100km)	46.5 mpg (6.08 l/100km)		
TRANSMISSION				
Туре	Automatic (CVT) with reverse function			
CHASSIS				
Front suspension	Double wishbone			
Front shocks type / travel	SACHS <sup>†</sup> Twin-tube coil-over shocks / 137 mm (5.39 in.)			
Rear suspension	Multi-link - mono swing arm			
Rear shocks type / travel	SACHS† Twin-tube coil-over shocks with preload adjustment / 150 mm (5.91 in.)			
Electronic brake distribution system	Foot-operated, hydraulic 3-wheel brake			
Front brakes	270 mm discs with Nissin 2-piston floating calipers			
Rear brake	220 mm disc, 1-pi	220 mm disc, 1-piston floating caliper		
Parking brake	Park lock			
Front tires	MC 145/60R16 66T			
Rear tire	MC 205/45R16 77T			
Aluminum front rims	5-spoke Carbon black, 406 x 114 mm (16 x 4.5 in.)			
Aluminum rear rim	5-spoke Carbon black, 406 x 165 mm (16 x 6.5 in.)			
CAPACITY				
Rider capacity	1			
Maximum vehicle load	204 kg (449.7 lb)			
Storage capacity	7 L (1.85 gal)			
Fuel capacity	20 L (5.28 gal)			
Fuel Type	Premium unleaded			

	Rotax® 600 ACE™	Rotax® 900 ACE™	
DIMENSIONS			
LxWxH	2,352 x 1,509 x 1,062 mm (92.6 x 59.4 x 41.8 in.)		
Wheelbase	1,709 mm (67.3 in.)		
Seat height	599 mm (23.6 in.)	597 mm (23.5 in.)	
Ground clearance	104 mm (4.1 in.)	102 mm (4.0 in.)	
Dry weight	270 kg (594 lb)	280 kg (616 lb)	
INSTRUMENTATION			
Туре	4.5" digital display		
Main Functions  SAFETY & SECURITY	Speedometer, tachometer, odometer, trips, distance to empty, engine lights, fuel gauge and clock	Speedometer, tachometer, odometer, trips, distance to empty, engine lights, fuel gauge, clock, ECO mode and Sport mode	
SCS	Stability Control System		
TCS	Traction Control System		
	Anti-lock Braking System		
ABS	Anti-lock Bra	aking System	
	<del></del>	aking System urity System (D.E.S.S.™)	
Anti-theft system	Digitally Encoded Secu	_ · ·	
ABS Anti-theft system HHC COVERAGE	Digitally Encoded Secu	urity System (D.E.S.S.™)	
Anti-theft system HHC	Digitally Encoded Secu Hill Hold	urity System (D.E.S.S.™)	
Anti-theft system HHC COVERAGE	Digitally Encoded Secu Hill Hold	urity System (D.E.S.S.™)	
Anti-theft system HHC COVERAGE Factory Warranty	Digitally Encoded Sect Hill Hold 2-year BRP Lir 2 halogen hea	urity System (D.E.S.S.™) d Control  inited Warranty  dlamps (55-W)	
Anti-theft system HHC COVERAGE Factory Warranty	Digitally Encoded Sect Hill Hold 2-year BRP Lir 2 halogen hea Front fenders with in	urity System (D.E.S.S.™) d Control  inited Warranty  dlamps (55-W) integrated LED lights	
Anti-theft system HHC COVERAGE Factory Warranty	Digitally Encoded Sect Hill Hold 2-year BRP Lir 2 halogen hea Front fenders with in	urity System (D.E.S.S.™) d Control  inited Warranty  dlamps (55-W)	

		SF	PORT / LETT / EC
Rotax® 900 ACE™	DIMENGIONO	Rotax® <b>600 ACE™</b>	Rotax® 900 ACE™
Rotax® 900 ACE™ in-line	LxWxH	2.2521.5001.002	(02 C F0 4 41 C in )
Rotax® 900 ACE: In In-line 3 cylinders, liquid-cooled with electronic fuel injection and electronic throttle control	Wheelbase	2,352 x 1,509 x 1,062 mm (92.6 x 59.4 x 41.8 in.) 1,709 mm (67.3 in.)	
		599 mm (23.6 in.)	597 mm (23.5 in.)
	Seat height Ground clearance	104 mm (4.1 in.)	102 mm (4.0 in.)
		270 kg (594 lb)	280 kg (616 lb)
74 x 69,7 mm (2.9 x 2.7 in.)	Dry weight	270 kg (594 lb)	280 kg (616 lb)
82 hp (61.1 kW) @ 8000 RPM	INSTRUMENTATION		
79.1 Nm (58.3 ft-lb)	Type 4.5" digital display		al display
@ 6500 RPM	Main Functions	Speedometer, tachometer,	Speedometer, tachometer,
143 g/km	-	odometer, trips, distance	odometer, trips, distance
46.5 mpg (6.08 l/100km)	-	to empty, engine lights, fuel gauge and clock	to empty, engine lights, fuel gauge, clock,
			ECO mode and Sport mode
vith reverse function	SAFETY & SECURITY		
	SCS	Stability Control System	
	TCS	Traction Control System	
wishbone	ABS	Anti-lock Braking System	
er shocks / 137 mm (5.39 in.)	Anti-theft system	Digitally Encoded Security System (D.E.S.S.™)	
ono swing arm	HHC	Hill Hold Control	
nocks with preload adjustment / (5.91 in.)	COVERAGE		
Iraulic 3-wheel brake	Factory Warranty	2-year BRP Limited Warranty	
n 2-piston floating calipers	- FEATURES		
ston floating caliper	FEATURES	Ohat I	
		2 halogen hea	dlamns (55-W)

#### CLASSIC SERIES<sup>1</sup>



Intense Black Adrenaline Red Yellow Shock

#### **EPIC SERIES**







## FEATURE HIGHLIGHTS



#### **AUTOMATIC TRANSMISSION (CVT)** No need to worry about changing gears as your contionusly variable tranmission will find the perfect combination of performance and fuel efficiency for you.



UFIT Can be adjusted tool-free to fit the rider and provide a personalized and comfortable riding experience.



**ENGINE OPTIONS** The 2-cylinder Rotax 600 ACE is the ultimate in accessible performance, while the 3-cylinder Rotax 900 ACE is the power & excitement standard of choice!



alignment or maintenance.



Vehicle Stability System that uses a variety of technologies, including SCS / ABS / TCS, to monitor the vehicle and keep the rider

#### **CUSTOMIZATION**

Can-Am Ryker was engineered to be almost infinitely customizable with 1 or 2-up options! Moments are all it takes to give it a transformation.

confident on the road.

<sup>1</sup>Choice of one set of Classic Panels included at the vehicle purchase. <sup>2</sup>Exclusive Panel Kits are available in limited quantities. \*2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. \*\*,\* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Vehicle performance may vary depending on weather, temperature, altitude, riding ability and rider/passenger's weight.

<sup>\*</sup>Only on Rotax 900 ACE Engine option