

2019 MXZ® BLIZZARD™

PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® and 600R E-TEC® engines
- RAS™ 3 front suspension
- REV® Gen4 platform with narrow-design bodywork
- pDrive™ clutch
- 15 x 129 x 1.25 in. Ice Ripper XT track
- Adjustable Pilot™ TS Skis
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Multifunction digital gauge with display
- Electric fuel gauge
- Ergo-Step side panels
- RF D.E.S.S.™ key
- Performance trail seat
- Warm glove box with 4 L / 1 US gal of storage
- Open toe-hold



MXZ® BLIZZARD 600R E-TEC® shown

ROTAX® ENGINE

	850 E-TEC®	600R E-TEC®
Engine details	Liquid-cooled, eRAVE™	Liquid-cooled, eRAVE™
Cylinders	2	2
Displacement	849 cc / 51.9 in. ³	599.4 cc / 36.6 in. ³
Bore	82 mm / 3.2 in.	72.3 mm / 2.85 in.
Stroke	80.4 mm / 3.2 in.	73 mm / 2.87 in.
Maximum engine speed	7,900 RPM	8,100 RPM
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection
Recommended fuel type	Premium unleaded	Premium unleaded
Minimum octane	91	91
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.4 L / 3.6 qt

POWERTRAIN

	850 E-TEC®	600R E-TEC®
Drive clutch type	pDrive™ with clickers	pDrive™
Driven clutch type	QRS	QRS
Engagement	3,800 RPM	3,400 RPM
Small sprocket number of teeth	27	23
Large sprocket number of teeth	45	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

850 E-TEC®	221 kg / 487 lb	600R E-TEC®	218 kg / 480 lb
------------	-----------------	-------------	-----------------

FEATURES

Frame	REV® Gen4	Riser block height	120 mm / 4.7 in.	Mirrors	Optional
Bodywork	Narrow design	Starter	Electric	Windshield	430 mm / 17 in.
Skis	Pilot™ TS	Reverse	RER™	Runner	Adjustable blade 1/4
Seating	Trail performance	Heated throttle lever/ grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	U-shaped aluminum with J-hooks	Gauge	Multifunction	Hitch	Optional