

# 2019 MXZ TNT®

## PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® and 600R E-TEC® engines
- RAS™ 3 front suspension
- REV® Gen4 platform with narrow-design bodywork
- pDrive™ clutch
- Ergo-Step side panels
- Open toe-hold
- rMotion™ rear suspension
- 15 x 129 x 1.25 in. RipSaw® track
- HPG™ Plus aluminum front shocks
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Warm glove box with 4 L / 1 US gal of storage
- RF D.E.S.S.™ key
- Medium (17 in.) windshield with air deflectors



MXZ® TNT 850 E-TEC® shown

## ROTAX® ENGINE

	850 E-TEC®	600R E-TEC®
Engine details	Liquid-cooled, eRAVE™	Liquid-cooled, eRAVE™
Cylinders	2	2
Displacement	849 cc / 51.9 in. <sup>3</sup>	599.4 cc / 36.6 in. <sup>3</sup>
Bore	82 mm / 3.2 in.	72.3 mm / 2.85 in.
Stroke	80.4 mm / 3.2 in.	73 mm / 2.87 in.
Maximum engine speed	7,900 RPM	8,100 RPM
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection
Recommended fuel type	Premium unleaded	Premium unleaded
Minimum octane	91	91
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.4 L / 3.6 qt

## POWERTRAIN

	850 E-TEC®	600R E-TEC®
Drive clutch type	pDrive™ with clickers	pDrive™
Driven clutch type	QRS	QRS
Engagement	3,800 RPM	3,400 RPM
Small sprocket number of teeth	27	23
Large sprocket number of teeth	45	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line

## DRY WEIGHT

850 E-TEC®	215 kg / 474 lb
600R E-TEC®	212 kg / 467 lb

## COLOR

White / Black

Black

## DIMENSIONS

Vehicle overall length	2,925 mm / 115.2 in.
Vehicle overall width	1,217 mm / 47.9 in.
Vehicle overall height	1,331 mm / 52.4 in.
Ski stance	1,077 mm / 42.4 in.
Ski overall length	1,066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3,269 mm / 129 in.
Track profile height	31.8 mm / 1.25 in. RipSaw®

## SUSPENSION

Front suspension	RAS™ 3
Front shock	HPG™ Plus
Front suspension max. travel	220 mm / 8.7 in.
Rear suspension	rMotion™
Center shock	HPG™ Plus
Rear shock	HPG™ Plus
Rear suspension max. travel	272 mm / 10.7 in.

## FEATURES

Frame	REV® Gen4	Riser block height	120 mm / 4.7 in.	Mirrors	Optional
Bodywork	Narrow design	Starter	Electric	Windshield	430 mm / 17 in.
Skis	Pilot™ 5.7	Reverse	RER™	Runner	Square 3/8
Seating	Trail performance	Heated throttle lever/ grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	U-shaped aluminum with J-hooks	Gauge	Analog with display	Hitch	Optional